



PRODUCTS

SM1500 SHOULDER PAVER



The ShoulderMaster SM1500 is a skidsteer/wheeled loader shoulder paving attachment that can increase the road shoulders from 0" to 4ft 2" wide.

- Lays asphalt and gravel materials
- The optimal hydraulic standard flow is 21 gal/min
- Minimum skid steer requirement 55kw
- Weight empty 4,263lbs
- Screed can drop below existing pavement only once fully extended to 4ft 3". Once fully extended it will drop 4" below and 2" above with gradients of 5%

PRODUCT SPECIFICATIONS - SM1500

Weight	4,263lbs
Length	10ft 2"
Height	3ft 11"
Screed Width adjustment	0' to 4ft 3"
Screed Height Adjustment for Pavement Level	-4" to +2"
Minimal Power Requirement	55kw
Optimal Hydraulic Flow	21gal/min
Screed Slope Adjustment	+/- 5 degrees
Drive Mechanism	Reduction Gearbox (Chain and Sprockets)
Conveyor	Chain drive with heat resistant belt
Electrical Connect	12V

FEATURES & BENEFITS

- Designed by the industry for the industry
- Lays asphalt and gravel materials
- Chain driven, heat rated belt to withstand asphalt
- Wireless remote control for operator safety
- Wireless camera with in cab monitor for ease of operation
- Screed dropping below existing pavement of 6" and 4" above at any width allowing you to precisely place materials in multiply layers with gradients up to 5%
- Universal skid steer attachment
- Bolt on exchangeable screed extensions
- Built tough to withstand harsh conditions

